The future of wet and dry vacuum cleaning

The VL500 series of wet and dry vacuum cleaners is offering performance and reliability that ensure low total cost of ownership and at the same time has features making daily cleaning tasks easier, faster and safer.
VL500 is ideally suited for hotels, contract cleaners, education, exhibition and conference centers as well as public buildings, manufacturing and industrial applications. A failsafe filter design makes operation easy due to the ability to have individual wet and dry filters working simultaneously. Each filter is specific for either a wet or dry application ensuring maximum performance. With the special dual filtration system, Nilfisk VL500 can be used in whatever environment, wet or dry, without the need to change filters. The unique design and features of VL500 is developed in partnership with Nilfisk customers. The VL500 is available in different configurations and various container sizes; 35, 55 and 75 liter.
Go to the specific factsheet for further information.



Picture shown may not represent model quoted

- Quick release adjustable push handle for easy and ergonomic maneuvering of the machine
- Emptying the container without having to remove the motor head makes operation fast and easy without risk of damage to critical components
- By transferring the weight as you lift the container, the Nilfisk Ergo Tipping system enables you to empty a completely filled container of fluid without excessive effort
- Easy changing of filters with the hinged motor head protects the machines and speeds up the process
- The VL500 can be used in both wet or dry applications without the need to change filters

● Standard equipment

Included accessories		Ref. no.	Min. required	VL500 75-1 BSF 220-240V/50-60 EU	VL500 75-2 BSF 220-240V/50-60 EU	VL500 75-2 EDF 220-240V/50-60 EU
Hose Vacuum Cleaner						
	HOSE D40 2.5M CPL	107407336	1	●	●	●
Vac Nozzle Wet						
	FLOOR NOZZLE D40 RUBBER STRIP	107407338	1			
	HARDFLOOR NOZZLE 400MM X Ø40MM - KIT	107416577	1	●	●	●
Hard Floor Nozzle						
	FLOOR NOZZLE D40 BRUSH	107407339	1	●	●	●
Crevice Nozzle						
	CREVICE NOZZLE D40	107408850	1	●	●	●
Filter						
	CARTRIDGE FILTER	107407300	1			●
	SACK FILTER	107407304	1	●	●	
Special Filter						

All information provided in this document is subject to change without prior notice

The future of wet and dry vacuum cleaning

Model	VL500 75-1 BSF 220-240V/50-60 EU	VL500 75-2 BSF 220-240V/50-60 EU	VL500 75-2 EDF 220-240V/50-60 EU
Ref. no.	107405158	107405159	107405164
PRODUCT FEATURES			
Dual power		•	•
Tube holder	•	•	•
Dual filter system			•
Folding transport handle			•
Adjustable handle			•
Storage of accessories	•	•	•
Drain hose	•	•	•
Ergo tipping			•

Model	VL500 75-2 EDF 220-240V/50 UK	VL500 75-2 EDF 220-240V/50 AU/NZ	VL500 75-2 EDF 230V/50 ZA
Ref. no.	107405174	107405185	107405203
PRODUCT FEATURES			
Dual power	•	•	•
Tube holder	•	•	•
Dual filter system	•	•	•
Folding transport handle	•	•	•
Adjustable handle	•	•	•
Storage of accessories	•	•	•
Drain hose	•	•	•
Ergo tipping	•	•	•

Model		VL500 75-2 EDF 230V/50HZ CN	VL500 75-2 BDF 220-240V/50-60HZ
Ref. no.		107405536	107407462
PRODUCT FEATURES			
Dual power		•	•
Tube holder		•	•
Dual filter system		•	•
Folding transport handle		•	
Adjustable handle		•	
Storage of accessories		•	•
Drain hose		•	•
Ergo tipping		•	

All information provided in this document is subject to change without prior notice

The future of wet and dry vacuum cleaning

Technical specifications	VL500 75-1 BSF 220-240V/50-60 EU	VL500 75-2 BSF 220-240V/50-60 EU	VL500 75-2 EDF 220-240V/50-60 EU
Plug type	EU	EU	EU
Cable length (m)/ plug type	10/EU	10/EU	10/EU
Voltage (V)	220-240	220-240	220-240
Frequency (Hz)	50-60	50-60	50-60
Voltage/frequency (V/Hz)	220-240/50-60	220-240/50-60	220-240/50-60
IP protection class	IP24	IP24	IP24
Rated power (W)	1350	2500	2500
Power Piec (W)	1250	2400	2400
Suction power end of tube (W)	200	200	200
Airflow (l/sec.)	48	72	72
Vacuum at nozzle (kPa)	20	21	21
Sound pressure level (dB(A) BS 5415)	64	66	66
Sound power level (dB(A) IEC 704)	82	84	84
Cable length (m)	10	10	10
Tank capacity (l)	75	75	75
Dust bag capacity (l)	44	44	44
Sack filter area (cm²)	1840	1840	-
Wet filter area (cm²)	-	-	1840
Cartridge filter area (optional) (cm²)	-	-	4410
Hose length (m)	2.5	2.5	2.5
Inlet (mm)	40	40	40
Length x width x height (mm)	840x620x1000	840x620x1000	660x620x1030
Weight (kg)	26	27	28.5

Technical specifications	VL500 75-2 EDF 220-240V/50 UK	VL500 75-2 EDF 220-240V/50 AU/NZ	VL500 75-2 EDF 230V/50 ZA
Plug type	UK	AU/NZ	ZA
Cable length (m)/ plug type	10/UK	10/AUS	10/ZA
Voltage (V)	220-240	220-240	220-240
Frequency (Hz)	50-60	50	50-60
Voltage/frequency (V/Hz)	220-240/50-60	220-240/50	220-240/50-60
IP protection class	IP24	IP24	IP24
Rated power (W)	2500	2500	2500
Power Piec (W)	2400	2400	2400
Suction power end of tube (W)	200	200	200
Airflow (l/sec.)	72	72	72
Vacuum at nozzle (kPa)	21	21	21
Sound pressure level (dB(A) BS 5415)	66	66	66

All information provided in this document is subject to change without prior notice

The future of wet and dry vacuum cleaning

Technical specifications	VL500 75-2 EDF 220-240V/50 UK	VL500 75-2 EDF 220-240V/50 AU/NZ	VL500 75-2 EDF 230V/50 ZA
Sound power level (dB(A) IEC 704)	84	84	84
Cable length (m)	10	10	10
Tank capacity (l)	75	75	75
Dust bag capacity (l)	44	44	44
Sack filter area (cm²)	-	-	-
Wet filter area (cm²)	1840	1840	1840
Cartridge filter area (optional) (cm²)	4410	4410	4410
Hose length (m)	2.5	2.5	2.5
Inlet (mm)	40	40	40
Length x width x height (mm)	660x620x1030	660x620x1030	660x620x1030
Weight (kg)	28.5	28.5	28.5

Technical specifications	VL500 75-2 EDF 230V/50HZ CN	VL500 75-2 BDF 220-240V/50-60HZ
Plug type	CN	EU
Cable length (m)/ plug type	10/CN	10/EU
Voltage (V)	220-240	220-240
Frequency (Hz)	50-60	50-60
Voltage/frequency (V/Hz)	220-240/50-60	220-240/50-60
IP protection class	IP24	IP24
Rated power (W)	2500	2500
Power Piec (W)	2400	2400
Suction power end of tube (W)	200	200
Airflow (l/sec.)	72	72
Vacuum at nozzle (kPa)	21	21
Sound pressure level (dB(A) BS 5415)	66	66
Sound power level (dB(A) IEC 704)	84	84
Cable length (m)	10	10
Tank capacity (l)	75	75
Dust bag capacity (l)	44	44
Sack filter area (cm²)	-	-
Wet filter area (cm²)	1840	1840
Cartridge filter area (optional) (cm²)	4410	4410
Hose length (m)	2.5	2.5
Inlet (mm)	40	40
Length x width x height (mm)	660x620x1030	840x620x1000
Weight (kg)	28.5	28

All information provided in this document is subject to change without prior notice